

Tender specifications

EC centrifugal fan modules – RadiPac

EC centrifugal fans – RadiPac

sizes 710 to 800

Direct-drive, single inlet centrifugal fans with backwards-curved high-performance centrifugal impellers, based on a GreenTech EC external rotor motor with integrated control electronics.

Impeller made of aluminum, with 7 backwards-curved, continuously welded blades; flow-optimized inlet ring made of galvanized sheet steel with pressure test nipple.

Motor-impeller in accordance with DIN ISO 21940, statically and dynamically balanced on two planes to balancing grade G 4.0.

GreenTech EC external rotor motors achieve or exceed the efficiency specifications in accordance with efficiency class IE5 (IEC TS 60034-30-2:2016), magnets without the use of rare earths, maintenance-free ball bearings with long-term lubrication, theoretical nominal service life of at least 40,000 operating hours.

Soft start, integrated current limitation, automatic resonance detection (from an input power of 2kW), extended voltage input 3~380-480 V, 50/60 Hz. The fan can be used with all standard power supply networks with unaltered air performance. Integrated control electronics, low-noise commutation logic; 100% speed control. All fans have an RS485/MODBUS RTU interface, no shielded cables are required for the power supply. Terminal box made of aluminum with easily accessible connection area, environment-resistant cable glands.

As a ready-to-install cube design intended exclusively for floor mounting. Struts made of extruded aluminum sections connected to die-cast corner plates, nozzle plate and inlet ring made of sendzimir galvanized sheet steel, motor mounting plate made of coated sheet steel. Not suitable for wall mounting.

Any work required for isolation from structure-borne noise is to be performed by the customer.

The fan satisfies the applicable EMC guidelines and requirements with regard to harmonic effects (see applicable data sheet for specific figures).

Documentation and marking in accordance with the applicable EU directives.

Reliable performance data, air performance measurements taken on an intake-side chamber test rig in accordance with ISO 5801 and DIN 24163. Noise measurements taken in an anechoic room in accordance with DIN EN ISO 3745.

Integrated protective devices:

- Alarm relay with floating contacts (250 V AC/2 A, $\cos \varphi = 1$)
- Locked-rotor protection
- Phase failure detection
- Soft start of motors
- Line undervoltage detection
- Thermal overload protection for electronics and motor
- Short circuit protection

Optional:

- **Other and specific requirements on request**

- **FlowGrid air inlet grill:**

FlowGrid air inlet grill tailor-made for the fan, to reduce assembly and system-related noise. FlowGrid made of high-grade composite material in one piece, available ready for installation and also suitable for retrofitting. Particularly suitable for confined intake conditions at the fan and/or if upstream turbulence-inducing fittings are unavoidable. The FlowGrid breaks up the turbulence fields and straightens the flow, resulting in distinct noise reduction.


Tender specifications

EC centrifugal fan modules – RadiPac


Technical data:

Fan type		=	_____	
Material number		=	_____	
Air flow	qV	=	_____	m ³ /h
Stat. pressure increase	p _{fs}	=	_____	Pa
Stat. overall efficiency	η _{esd}	=	_____	%
Operating speed	n	=	_____	rpm
Motor type		=	EC motor	
Type of control		=	Speed control, 0-100%	
Motor efficiency class		=	IE5	
Total power consumption	P _{ed}	=	_____	kW
Specific fan power	SFP	=	_____	kW/(m ³ /s)
Nominal voltage	U _N	=	_____	V
Line frequency	f	=	50 / 60	Hz
Nominal current	I _N	=	_____	A
Protection class		=	IP55	
Sound power level	L _{WA} (A, in)	=	_____ / L _{WA} (A, out) = _____	dB(A)
Sound pressure level (at 1 m)	L _{pA} (A, in)	=	_____ / L _{pA} (A, out) = _____	dB(A)
Permissible ambient temperature	T	=	_____ to _____	°C
Fan weight	m	=	_____	kg

Product photo



RadiPac EC centrifugal fans
 Cube design
 Fan sizes 710 – 800



FlowGrid air inlet grill
 Optional

See data sheet for dimensions and connections